


Top Access Clean Room Fluorescent Fittings



Model : KMR 240 Clean Room

Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.	
Reflector	: Pre - anodised aluminium sheet.	
Diffuser	: M12 Acrylic diffuser.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
IP Protection	: IP 20	
Mechanical Mounting	: Recessed wall mounting.	
Hole Opening Dimension	: 383mm W x 1,248mm L	
Expose Frame Dimension	: 410mm W x 1,273mm L x 100mm Ht.	
Lamp Source	: Fluorescent lamp 2 x 36W or 3 x 36W / 865 superdaylite (240V 50 Hz)	
Ballast	: 6W extra low loss ballast.	
Optional Components	: High frequency electronic ballast.	(EB)
	: EL emergency power pack.	(EL)
	: 2 amp Fused terminal block.	(FTB)
	: Radio interference suppressors.	(RIS)
Applications	: Clean room.	

Ordering Code

Example : KMR240 Clean Room

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027-W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@kohsun.com