

Surface Mounted Diffuser Fluorescent Fittings

This surface mounted luminaire is designed to meet the performance of visual comfort and appearance.



Model : KD140/PLL or KD 240/PLL

Technical Data

| | |
|---------------------|---|
| Construction | : In heavy gauge steel sheet and fully pre-treated. |
| Diffuser | : M12 Acrylic diffuser. |
| Paintwork | : High grade white polyester powder coated high reflectance finish. |
| IP Protection | : IP 20 |
| Mechanical Mounting | : Surface or wall mounted. |
| Dimension | : 265mm Width x 520mm Length x 80mm Height |
| Lamp Source | : Compact fluorescent lamp 1 or 2 x PLL36W (240V 50Hz) |
| Ballast | : 6W extra low loss ballast. |
| Optional Components | : High frequency electronic ballast. (EB) |
| Applications | : Corridors and Staircase areas. |

Ordering Code

Example : KD240/PLL

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027-W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara,
47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@kohsun.com

Rev. A