

## Recessed White Coated Reflector Fluorescent Fittings

This is a high efficiency recessed luminaire. The high efficiency white epoxy coated reflector provides a batwing light distribution and permits extended spacing between luminaires without loss of uniformity. The reflector is hinged to the housing allowing easy maintenance.



**Model : KSC/AR 440 White**

### Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.	
Louvre	: Aluminium reflector with high grade white polyester powder coated high reflectance finish.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
IP Protection	: IP 20	
Mechanical Mounting	: T - Bar suspended ceiling. ( Recessed Type )	
Hole Opening Dimension	: 595mm W x 1,195mm L ( Metric ) or 603mm W x 1,212mm L ( Imperial )	
Expose Frame Dimension	: 595mm W ( Metric ) or 603mm W ( Imperial ) x 1,223mm L x 93mm Ht.	
Lamp Source	: Fluorescent lamp 4 x 36W ( 240V 50Hz )	
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K	
Ballast	: 6W extra low loss ballast.	
Optional Components	: High frequency electronic ballast. ( EB ) : EL emergency power pack. ( EL ) : 2 amp Fused terminal block. ( FTB ) : Radio interference suppressors. ( RIS )	
Applications	: Department stores, Reception areas, Halls, Showroom and Libraries.	

### Ordering Code

**Example : KSC/AR440 White / 2' X 4' / TM / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027-W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@kohsun.com