

Suspended T5 Luminaire

This T5 high efficiency luminaire with superior internal reflector design achieving high output of 92% offers ideal combination of stylish design and optimum performance for both task and general lighting. Suitable for use where cost saving and energy efficiency is important.



Model : KTF - 2F S-HO

Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.
Reflector	: High quality & 95% reflectance aluminium.
Paintwork	: High grade grey polyester powder coated high reflectance finish.
Mechanical Mounting	: Suspended With 2 nos of steel-wire suspensions.
Dimension	: 300 mm Width x 1,195mm Length x 68mm Height.
Lamp Source	: 2 x 54W HO
IP Protection	: IP 20
Ballast	: Electronic control gear with auto - voltage regulation from 198 - 264V fluctuates and lifetime up to 50,000 hours*.
Features	: Maximize energy savings by up to 45% : Easy to maintain - Back ballast access, replace w/o touching reflector : Flexible installation - Suspended by steel wire with adjuster. : Rapid re-start (not possible with HID lamps) : Low harmonic distortion certified to EN610003-2 : High power factor min. 0.97 : Safe shutdown of faulty lamps : 2 amp Fused terminal block for easy future maintenance : Opal diffuser
Optional Components	: Digital addressable lighting interface (DALI) ballast : Motion sensor & lux sensor
Applications	: Computer rooms, Airports, Hospital, Libraries and Department stores.
* Conditions applied	

Ordering Code

Example : KTF - 2F S-HO

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.