

T-5 Bare Channel Fittings with Aluminium Reflector

This T-5 fluorescent architectural fixture with integral ballast provides maximum efficiency with high quality & 95% reflectance diamond shaped bended aluminium reflector.



Model : KTFB - 2F / HO aluminium reflector

Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.		
Paintwork	: High grade white polyester powder coated high reflectance finish.		
Reflector	: High quality & 95% reflectance aluminium. (Miro 4)		
IP Protection	: IP 20		
Mechanical Mounting	: Surface or wall mounted.		
Dimension	: KTFB - 2T / HO	2 x 24W	123mm Width x 571mm Length x 70mm Height
	: KTFB - 2T	2 x 14W	123mm Width x 571mm Length x 70mm Height
	: KTFB - 2T / HO	2 x 24W	123mm Width x 571mm Length x 70mm Height
	: KTFB - 2F	2 x 28W	123mm Width x 1,171mm Length x 70mm Height
	: KTFB - 2F / HO	2 x 54W	123mm Width x 1,171mm Length x 70mm Height
	: KTFB - 2FF	2 x 35W	123mm Width x 1,471mm Length x 70mm Height
	: KTFB - 2FF - HO	2 x 80W	123mm Width x 1,471mm Length x 70mm Height
Lamp Source	: T-5 Fluorescent lamp		
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K		
Ballast	: Philips / Osram or equivalent.		
Optional Components	: Dimmable ballast.		
Applications	: Hypermarket, Storage plants, Factories, Garages, Car park.		

Ordering Code

Example : KTFB - 2F / HO aluminium reflector

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027-W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@kohsun.com