

## Anti Corrosive Fluorescent Fittings

IP65 rating anti corrosive fluorescent fitting. This fitting is total protection against dust and water jets.



**Model : KTFC - 2F**

### Technical Data

Body	: Made of reinforced polyester with fibreglass. ( GRP )
Diffuser	: Prismatic type clear acrylic injected, UV stable with angles studied for total transparency.
Tightness	: Safety clips. ( 4nos for 14W & 24W, 6nos for 28W & 54W, 8nos for 35W & 80W )
IP Protection	: IP65, with total protection against dust and water jets.
Mechanical Mounting	: Surface or wall mounted.
Dimension	: KTFC - 1T 1 x 14W or KTFC - 1T / HO 1 x 24W 100mmW x 666mmL x 108mmHt. : KTFC - 2T 2 x 14W or KTFC - 2T / HO 2 x 24W 100mmW x 666mmL x 108mmHt. : KTFC - 1F 1 x 28W or KTFC - 1F / HO 1 x 54W 100mmW x 1,276mmL x 108mmHt. : KTFC - 2F 2 x 28W or KTFC - 2F / HO 2 x 54W 100mmW x 1,276mmL x 108mmHt. : KTFC - 1FF 1 x 35W or KTFC - 1FF / HO 1 x 80W 100mmW x 1,576mmL x 108mmHt. : KTFC - 2FF 2 x 35W or KTFC - 2FF / HO 2 x 80W 100mmW x 1,576mmL x 108mmHt.
Lamp Source	: T-5 Fluorescent lamp
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K
Ballast	: Philips / Osram or equivalent.
Optional Components	: Dimmable ballast.
Applications	: Humid and dusty areas, Food processing areas and Room with corrosive vapours.

### Ordering Code

**Example : KTFC - 2F**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027-W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@kohsun.com