


Hospital Operation Theatre Fluorescent Fittings



Model : KMR340 OT

Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.	
Diffuser	: M12 Acrylic diffuser.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
IP Protection	: IP 20	
Mechanical Mounting	: Plaster ceiling or Wood ceiling.	
Dimension	: 358mm Width x 1,226mm Length x 100mm Height	
Frame Dimension	: 410mm Width x 1,250mm Length	
Lamp Source	: Fluorescent lamp 3 x 36W (240V 50Hz)	
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K	
Ballast	: 6W extra low loss ballast.	
Optional Components	: High frequency electronic ballast.	(EB)
	: 2 amp Fused terminal block.	(FTB)
	: Radio interference suppressors.	(RIS)

Ordering Code

Example : KMR340 OT

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027-W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@kohsun.com

Rev. A