

## Bare Channel Mirror Reflector Fluorescent Fittings

This luminaire is a combination of fittings and open-ended reflector. The reflector provides a higher downward light output ratio and is recommended for use where illumination is required to concentrate at certain areas. Suitable for ceiling mounting or pendant mounted by suspension rods.



**Model : KR 240 Mirror**

### Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.
Paintwork	: High grade white polyester powder coated high reflectance finish.
IP Protection	: IP 20
Mechanical Mounting	: Surface or wall mounted.
Dimension	: KR120 1 x 18W = 138mmW x 610mmL x 85mmHt. : KR220 2 x 18W = 208mmW x 610mmL x 85mmHt. : KR140 1 x 36W = 138mmW x 1,220mmL x 85mmHt. : KR240 2 x 36W = 208mmW x 1,220mmL x 85mmHt. : KR340 3 x 36W = 250mmW x 1,220mmL x 85mmHt.
Lamp Source	: Fluorescent lamp 18W or 36W ( 240V 50Hz )
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K
Ballast	: 6W extra low loss ballast.
Optional Components	: High frequency electronic ballast. ( EB ) : EL emergency power pack. ( EL ) : 2 amp Fused terminal block. ( FTB ) : Radio interference suppressors. ( RIS )
Applications	: Workshops, Warehouses, Factories and Industrial production line.

### Ordering Code

**Example : KR 240 / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027-W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@kohsun.com