

## Bare Channel Wire-Guard Fluorescent Fittings

This luminaire is designed for use in areas where security of the tube are necessary. The wire guard is hinged on one side of the casing and secured on the other side by a pad lock.



**Model : KWG 140 / KWG 240**

### Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
IP Protection	: IP 20	
Mechanical Mounting	: Surface or wall mounted.	
Dimension	: KWG120 1 x 18W = 105mmW x 610mmL x 110mmHt. : KWG220 2 x 18W = 155mmW x 610mmL x 115mmHt. : KWG140 1 x 36W = 105mmW x 1,220mmL x 110mmHt. : KWG240 2 x 36W = 155mmW x 1,220mmL x 115mmHt.	
Lamp Source	: Fluorescent lamp 18W or 36W ( 240V 50Hz )	
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K	
Ballast	: 6W extra low loss ballast.	
Optional Components	: High frequency electronic ballast. ( EB ) : EL emergency power pack. ( EL ) : 2 amp Fused terminal block. ( FTB ) : Radio interference suppressors. ( RIS )	
Applications	: Car park & similar location where vandalism and breakage occurs quite frequently.	

### Ordering Code

**Example : KWG 140 / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027-W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@kohsun.com