

## Bare Channel Wire-Guard Fluorescent Fittings

This luminaire is designed for use in areas where security of the tube are necessary. The wire guard is secured with wire mesh with end caps.



### Model : KWG 240

#### Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
IP Protection	: IP 20	
Mechanical Mounting	: Surface or wall mounted.	
Dimension	: KWG220 2 x 18W = 105mmW x 616mmL x 100mmHt. : KWG240 2 x 36W = 105mmW x 1,225mmL x 100mmHt.	
Lamp Source	: Fluorescent lamp 18W or 36W ( 240V 50Hz )	
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K	
Ballast	: 6W extra low loss ballast.	
Optional Components	: High frequency electronic ballast. ( EB ) : EL emergency power pack. ( EL ) : 2 amp Fused terminal block. ( FTB ) : Radio interference suppressors. ( RIS )	
Applications	: Car park & similar location where vandalism and breakage occurs quite frequently.	

#### Ordering Code

**Example : KWG 240 / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027-W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@kohsun.com