

## PLL36W VDU Parabolic Louvre Fluorescent Fittings

This modular recessed luminaire is fitted with PLL36W lamp in combination with the VDU parabolic louvre provides optimum lighting performance.



**Model : KMR/AR 340 PLL 16 cells**

### Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.	
Louvre	: High quality, chemically brightened and anodized in semi-gloss or gloss finish. Parabolic shaped vanes ensure high efficiency optimal light output with wide batwing distribution, good uniformity and low glare.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
IP Protection	: IP 20	
Mechanical Mounting	: Wood ceiling or plaster ceiling.	
Hole Opening Dimension	: 490mm W x 490mm L	
Expose Frame Dimension	: 530mm W x 530mm L x 95mm Ht.	
Lamp Source	: Fluorescent lamp PLL36W ( 240V 50Hz )	
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K	
Ballast	: 6W extra low loss ballast.	
Optional Components	: High frequency electronic ballast. ( EB ) : Top mirror. ( TM ) : EL emergency power pack. ( EL ) : 2 amp Fused terminal block. ( FTB ) : Radio interference suppressors. ( RIS )	
Applications	: Computer rooms, Airports, Hospitals, Reception areas, Libraries and Department stores.	

### Ordering Code

**Example : KMR/AR340 PLL / SF / TM / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027-W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@kohsun.com