

Modular Recessed Parabolic Louvre Fluorescent Fittings

This is a high efficiency modular recessed luminaire. The high efficiency parabolic reflector provides a batwing light distribution and permits extended spacing between luminaires without loss of uniformity. The reflector is hinged to the housing allowing easy maintenance.



Model : KMR/AR 420

Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.	
Louvre	: High quality, chemically brightened and anodized in semi-gloss or gloss finish. Parabolic shaped vanes ensure high efficiency optimal light output with wide batwing distribution, good uniformity and low glare.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
IP Protection	: IP 20	
Mechanical Mounting	: Plaster ceiling or Wood ceiling.	
External Dimension	: 635mm W x 635mm L x 93mm Ht.	
Opening Dimension	: 612mm W x 612mm L	
Lamp Source	: Fluorescent lamp 4 x 18W (240V 50Hz)	
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K	
Ballast	: 6W extra low loss ballast.	
Optional Components	: High frequency electronic ballast. (EB) : Top mirror. (TM) : EL emergency power pack. (EL) : 2 amp Fused terminal block. (FTB) : Radio interference suppressors. (RIS)	
Applications	: Offices, Department stores, Reception areas, Halls, Showroom and Libraries.	

Ordering Code

Example : KMR/AR 420

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027-W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@kohsun.com