

Modular Recessed Parabolic Louvre Fluorescent Fittings

This is a high efficiency modular recessed luminaire. The high efficiency parabolic reflector provides a batwing light distribution and permits extended spacing between luminaires without loss of uniformity. The reflector is hinged to the housing allowing easy maintenance.



Model : KMR/AR 240

Technical Data

| | | |
|-------------------------|--|--|
| Construction | : In heavy gauge steel sheet and fully pre-treated. | |
| Louvre | : High quality, chemically brightened and anodized in semi-gloss or gloss finish. Parabolic shaped vanes ensure high efficiency optimal light output with wide batwing distribution, good uniformity and low glare. | |
| Paintwork | : High grade white polyester powder coated high reflectance finish. | |
| IP Protection | : IP 20 | |
| Mechanical Mounting | : Plaster ceiling or Wood ceiling. | |
| External Dimension | : 330mm W x 1,250mm L x 93mm Ht. | |
| Opening Dimension | : 308mm W x 1,225mm L | |
| Lamp Source | : Fluorescent lamp 2 x 36W (240V 50Hz) | |
| Lamp Colour Temperature | : 2,700K / 3,000K / 4,000K or 6,500K | |
| Ballast | : 6W extra low loss ballast. | |
| Optional Components | <ul style="list-style-type: none"> : High frequency electronic ballast. (EB) : Top mirror. (TM) : EL emergency power pack. (EL) : 2 amp Fused terminal block. (FTB) : Radio interference suppressors. (RIS) | |
| Applications | : Offices, Department stores, Reception areas, Halls, Showroom and Libraries. | |

Ordering Code

Example : KMR/AR 240

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027-W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@kohsun.com