

Recessed Hinged Diffuser Fluorescent Fittings

This recessed luminaire is designed for exposed Tee-Bar suspended ceiling with hinged diffuser for easy maintenance. The diffuser is framed in steel with spring loaded hinged and latches. The luminaire can also be supplied with two air slots along both sides of the luminaire which can be used for air-handling purposes.



Model : KSC/HD/AH 240

Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.	
Diffuser	: M12 Acrylic diffuser.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
IP Protection	: IP 20	
Mechanical Mounting	: T - Bar suspended ceiling. (Recessed Type)	
Dimension	: 2' x 2' = 603mmW (Imperial) or 595mmW (Metric) x 613mmL x 105mmHt. : 2' x 4' = 603mmW (Imperial) or 595mmW (Metric) x 1,223mmL x 105mmHt.	
Lamp Source	: Fluorescent lamp 18W or 36W (240V 50Hz)	
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K	
Ballast	: 6W extra low loss ballast.	
Optional Components	: Opal. (O) : Parabol louvre. (P L) : High frequency electronic ballast. (EB) : EL emergency power pack. (EL) : 2 amp Fused terminal block. (FTB) : Radio interference suppressors. (RIS)	
Applications	: Offices, Libraries, Halls, Hospital and Offices.	

Ordering Code

Example : KSC/HD/AH240 / 2' X 4' / EL / FTB / RIS

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027-W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@kohsun.com