

## Suspended Ceiling Fluorescent Fittings

This fully recessed luminaire is designed for exposed Tee-Bar suspended ceiling with a wide range of diffuser to suit individuals taste and preferences.



**Model : KSC 240**

### Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.	
Diffuser	: M12 Acrylic diffuser.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
IP Protection	: IP 20	
Mechanical Mounting	: T - Bar suspended ceiling. ( Recessed Type )	
Dimension	: KSC140 1 x 36W = 298mmW ( Imperial ) or 295mmW ( Metric ) x 1223mmL x 105mmHt. : KSC240 2 x 36W = 298mmW ( Imperial ) or 295mmW ( Metric ) x 1223mmL x 105mmHt. : KSC240 2 x 36W = 603mmW ( Imperial ) or 595mmW ( Metric ) x 1223mmL x 105mmHt. : KSC340 3 x 36W = 603mmW ( Imperial ) or 595mmW ( Metric ) x 1223mmL x 105mmHt. : KSC440 4 x 36W = 603mmW ( Imperial ) or 595mmW ( Metric ) x 1223mmL x 105mmHt.	
Lamp Source	: Fluorescent lamp 36W ( 240V 50Hz )	
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K	
Ballast	: 6W extra low loss ballast.	
Optional Components	: Opal. ( O ) : Parabol louvre. ( P L ) : High frequency electronic ballast. ( EB ) : EL emergency power pack. ( EL ) : 2 amp Fused terminal block. ( FTB ) : Radio interference suppressors. ( RIS )	
Applications	: Offices, Libraries and Department stores.	

### Ordering Code

**Example : KSC240 / 1' X 4' / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027-W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@kohsun.com