

Fluorescent Fittings With Side Metal Reflector

This recessed luminaire has been specially designed to produce a symmetrical downward light distribution.



Model : KSC/SR 340

Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
IP Protection	: IP 20	
Mechanical Mounting	: T - Bar suspended ceiling. (Recessed Type)	
Dimension	: KSC/SR220 2 x 18W = 603mmW (Imperial) or 595mmW (Metric) x 613mmL x 96mmHt. : KSC/SR320 3 x 18W = 603mmW (Imperial) or 595mmW (Metric) x 613mmL x 96mmHt. : KSC/SR420 4 x 18W = 603mmW (Imperial) or 595mmW (Metric) x 613mmL x 96mmHt. : KSC/SR240 2 x 36W = 603mmW (Imperial) or 595mmW (Metric) x 1,223mmL x 96mmHt. : KSC/SR340 3 x 36W = 603mmW (Imperial) or 595mmW (Metric) x 1,223mmL x 96mmHt. : KSC/SR440 4 x 36W = 603mmW (Imperial) or 595mmW (Metric) x 1,223mmL x 96mmHt.	
Lamp Source	: Fluorescent lamp 18W or 36W (240V 50Hz)	
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K	
Ballast	: 6W extra low loss ballast.	
Optional Components	High frequency electronic ballast.	(EB)
	EL emergency power pack.	(EL)
	2 amp Fused terminal block.	(FTB)
	Radio interference suppressors.	(RIS)
Applications	: Electronic factories and Assembly lines.	

Ordering Code

Example : KSC/SR340 / 2' X 4' / EL / FTB / RIS

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027-W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@kohsun.com