

## Fluorescent Fittings With Internal Metal Reflector

This recessed luminaire has been specially designed to produce a symmetrical downward light distribution.



**Model : KSC/IMR 340**

### Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
IP Protection	: IP 20	
Mechanical Mounting	: T - Bar suspended ceiling. ( Recessed Type )	
Dimension	: KSC/IMR220 2 x 18W =603mmW ( Imperial ) or 595mmW ( Metric ) x 613mmL x 96mmHt. : KSC/IMR320 3 x 18W =603mmW ( Imperial ) or 595mmW ( Metric ) x 613mmL x 96mmHt. : KSC/IMR240 2 x 36W =603mmW ( Imperial ) or 595mmW ( Metric ) x 1,223mmL x 96mmHt. : KSC/IMR340 3 x 36W =603mmW ( Imperial ) or 595mmW ( Metric ) x 1,223mmL x 96mmHt.	
Lamp Source	: Fluorescent lamp 18W or 36W ( 240V 50Hz )	
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K	
Ballast	: 6W extra low loss ballast.	
Optional Components	: High frequency electronic ballast.	( EB )
	: EL emergency power pack.	( EL )
	: 2 amp Fused terminal block.	( FTB )
	: Radio interference suppressors.	( RIS )
Applications	: Electronic factories and Assembly lines.	

### Ordering Code

**Example : KSC/IMR340 / 2' X 4' / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027-W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@kohsun.com

Rev. A