

Modular Recessed Fluorescent Fittings

This quality recessed luminaire is design to suit almost any ceiling. The flushed-looking provides strong appeal as well as good illumination for visual comfort.



Model : KMR 240 2' x 4'

Technical Data

Construction	: In heavy gauge steel sheet and fully pre-treated.
Diffuser	: M12 Acrylic diffuser.
Paintwork	: High grade white polyester powder coated high reflectance finish.
IP Protection	: IP 20
Mechanical Mounting	: Wood ceiling or plaster ceiling.
Dimension	: (Opening Dimension) : KMR240 2 x 36W = 330mmW x 1,248mmL x 83mmHt. (308mmW x 1,225mm L) : KMR240 2 x 36W = 636mmW x 1,248mmL x 83mmHt. (612mmW x 1,225mm L) : KMR340 3 x 36W = 636mmW x 1,248mmL x 83mmHt. (612mmW x 1,225mm L) : KMR440 4 x 36W = 636mmW x 1,248mmL x 83mmHt. (612mmW x 1,225mm L)
Lamp Source	: Fluorescent lamp 36W (240V 50Hz)
Lamp Colour Temperature	: 2,700K / 3,000K / 4,000K or 6,500K
Ballast	: 6W extra low loss ballast.
Optional Components	: Opal. (O) : Parabol louvre. (P L) : High frequency electronic ballast. (EB) : EL emergency power pack. (EL) : 2 amp Fused terminal block. (FTB) : Radio interference suppressors. (RIS)
Applications	: Offices, Libraries and Department stores.

Ordering Code

Example : KMR240 / 2' X 4' / EL / FTB / RIS

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change w/o prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027-W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, 47180 Puchong, Selangor D.E, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@kohsun.com